

TULLYMAC COLD LAY MACADAM

Product Information Sheet

Tullymac is the name given to our Cold Lay Macadam, which is blended, tested and packaged to the highest ISO9001 quality standards. Tullymac is a deferred set mixture ready to use straight from the bag for quick, cost effective repairs to footways, driveways and for all road maintenance.

Supply & Storage:

- Tullymac is available in handy 25kg bags or bulk for bigger jobs meaning wastage is minimal.
- Always ensure that the bags are kept sealed.
- Always ensure the material is stored in a well-ventilated area, away from all forms of heat.
- Tullymac Cold Lay Macadam can be stored for long periods with a shelf life of over 4 months.

Laying Guidelines:

- Ensure the area where Tullymac is to be laid is dry and firm.
- Sweep the area to be repaired and remove all weeds.
- Before overlaying concrete, spray or brush on a tack coat of bitumen emulsion.
- Laying equipment should incl. a rake, spade or trowel, roller or a flat object for tamping.
- Ensure the roller or tamper is kept wet so the Tullymac won't be "picked up" by the tools.
- On completion, a little dry sand or dust can be brushed over the finished surface, this will help prevent "picking up" of the fresh material as it sets. This is not essential but may be useful when the material is laid during warm weather.
- When reinstating deep potholes "> 40mm" Tullymac should be placed in two layers.
- Do not leave any objects on the freshly laid material & allow the Tullymac to fully harden.
- Always clean all equipment and tools on completion of work.
- After prolonged storage it may be necessary to expose the bag of Tullymac to direct sunlight for 1 to 2 hours to loosen the material and to restore workability.
- The more rolling or tamping to the surface, the more effective the reinstatement will be.
- The time taken for the Tullymac Cold Lay Macadam to harden fully will depend on the amount of compaction and ambient temperature.
- Health and Safety advice can be found in the Tullymac Safety Data Sheet.

Technical, pricing or ordering information regarding Tullymac Cold Lay Macadam can be obtained using our web site or by telephone (028)4066 2481 asking for either John McCartan or Derek Bailey.

